Bronze Threaded Ends Swing Check Valve

Feature

 \mathbf{D}

150# WSP / 300# WOG Bronze body Bronze disc FNPT x FNPT Threaded ends (ASME B1.20.1-NPT) Swing check "Y" Pattern MSS-SP-80





Pressure/ Temperature rating				
300 psi from 15 °F to 150 °F	180 psi max. at 350 °F			

* Max. temperature: 450°F

Material

	Part	Material	Specification	
1	Body	Bronze ASTM B62		
2	Сар	Brass	Brass ASTM B124 C37700	
3	Disc	Bronze ASTM B62		
4	Disc nut	Brass ASTM B124 C3770		
5	Hinge pin	Copper -		
6	Plug	Brass	ASTM B124 C37700	
7	Arm	Bronze	Bronze ASTM B62	





Dimension

	H [in]	L [in]	S [in]	Cv	Wt. [lb]
3/8"	1.54	2.13	0.91	3	0.48
1⁄2"	1.54	2.26	1.06	4	0.58
3/4"	1.93	2.84	1.29	8	0.92
1"	2.28	3.31	1.16	15	1.33
1 ¼"	2.76	3.90	2.01	26	2.23
1 ½"	3.11	4.45	2.28	37	3.24
2"	3.74	5.16	2.80	68	4.60
2 ½"	4.49	6.38	3.46	94	9.86
3"	5.20	7.32	4.02	133	14.74



redwhitevalvecorp.com

MARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www. P65Warnings.ca.gov.

Drawings, photos and data are provided for information only and subject to change without notice. No part of this document may be reproduced, copied, modified or adapted, without the prior written consent of the copyright owner, unless otherwise indicated.