Lead Free Solder Gate Valve

Feature

200# WOG Lead free brass body Solder x Solder Solder ends (ASME B16.22) Screw in bonnet Non-rising stem Solid disc AB1953, NSF/ANSI 61 & 372 certified






Pressure/ Temperature rating					
200# WOG	max. at 212 °F				

Material

	Part	Material	Specification	
1	Body	Lead Free Brass	ASTM B927 C28500	
2	Bonnet	Lead Free Brass	ASTM B927 C28500	
3	Stem	Lead Free Brass	ASTM B927 C28500	
4	Disc	Lead Free Brass	ASTM B927 C28500	
5	Lock nut	Lead Free Brass	ASTM B927 C28500	
6	Grand nut	Brass	ASTM B124	
7	Gland	Brass	ASTM B124	
8	Packing	PTFE	-	
9	Handwheel	Aluminum	-	
10	Nut	Steel	A36	
11	Tag	Aluminum	-	
12	Gasket	PTFE	-	



Dimension, Weight

Size	Φ [in]	D [in]	H [in]	L [in]	Wt.
1/2"	0.627-0.631	1.78	2.75	1.60	0.36
3/4"	0.877-0.881	1.78	3.18	2.00	0.56
1"	1.128-1.131	2.05	3.50	2.28	0.74
11/4"	1.378-1.381	2.38	4.35	2.91	1.36
11/2"	1.628-1.632	2.38	4.75	3.18	1.64
2"	2.128-2.132	3.12	5.60	3.62	2.52

