

DZR Lead Free Brass High Velocity Pump Flange Ball Valve


Feature

- 250# WOG
- DZR lead free brass body
- Chrome plated ball
- Full port
- ¼-turn operation
- Virgin PTFE seats
- Blow-out proof stem
- 3-piece construction
- EzPress x Flange
- Rotating flange design with slotted holes to ensure compatibility with standard and high velocity pumps
- Conical inlet to minimize turbulence
- Designed with side drain valve & cap
- Includes bolt kit, wing handle and gasket
- AB 1953, NSF/ANSI/CAN 61 & 372 certified



Material

	Part	Material	Specification
1	Body	DZR Lead Free Brass	ASTM B927 C27453
2	Flange	Brass	ASTM B283 C37700
3	Ball	DZR Lead Free Brass	ASTM B927 C27453
4	Seat	PTFE	
5	Fixed End	DZR Lead Free Brass	ASTM B927 C27453
6	O-Ring	EPDM Perox	NSF Approved
7	Stem	DZR Lead Free Brass	ASTM B927 C27453
8	Packing Ring	PTFE	
9	Packing Nut	Brass	ASTM B124 C37700
10	Red Handle Fig. 2412ABHV	Steel / Dacromet® Plated	ASTM A36
11	Nut	Steel / Zinc Plated	ASTM A36
12	Ball Valve	Brass	ASTM B283 C37700



Dimension, Weight

	B (in)	C (in)	C1 (in)	D (in)	E (in)	ØF (in)	ØG (in)	H (in)	I1 (in)	I2 (in)	L (in)	ØP (in)	ØN (in)	Weight (lb)	
3/4"	0.89	3.30	4.70	0.98	4.13	2.75	0.50	2.56	2.20	3.13	3.50	3.60	0.73	1.50	1.09
1"	1.14	3.81	6.29	1.06	4.13	2.75	0.50	2.71	2.56	3.13	3.50	4.98	0.98	1.50	1.49
1 1/4"	1.39	4.06	6.26	1.06	4.13	2.75	0.50	2.88	2.76	3.13	3.50	4.98	1.23	1.50	1.71
1 1/2"	1.64	5.12	7.70	1.26	4.13	2.75	0.50	2.99	3.15	3.13	3.50	5.57	1.46	1.50	2.74
2"	2.14	6.17	8.09	1.52	5.00	3.06	0.50	3.28	3.50	3.32	3.69	5.57	1.95	2.13	4.08

